



#### **Product features**

- Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps
- The versatile  $\dot{\text{ToLEDo}}$  Retro ball range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- Gives same sparkling light effect as the incandescent lamp
- Dimensionally identical to incandescent lamps fits all fixtures
- Environment-friendly no mercury and lower CO2 emissions
- Dimmable with approved dimmers













#### PRODUCT OVERVIEW

Product name	ToLEDo RT Ball V5 ST DIM 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	4.5
Туре	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740942
Warranty	3 years
Luminous flux (Im)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Wattage (W)	4.5
Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	15000
Product EAN number	5410288294933

#### **DATA TABLE**

Genera	l data
--------	--------

Product name ToLEDo RT Ball V5 ST DIM 470LM 827 E27 SL



### ToLEDo Retro Ball Dimmable

ToLEDo RT Ball V5 ST DIM 470LM 827 E27 SL 0029493

Toohnology	LED
Technology Watt (Rated) (W)	4.5
	LED exchangeable
Type Cap/Base	E27
Fixture rating	
<u> </u>	Open
General application	Hospitality, Residential & Consumer -10°C - 45°C
Operating temperature range (°C)	
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740942
Warranty	3 years
Optical data	
Luminous flux (Im)	470
Luminous flux (Rated) (Im)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal	70
life (%) Electrical data	
Wattage (W)	4.5
Equivalent watt (W)	40
Product Voltage (V)	230
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
Dimmable	Yes
Inrush Current (A)	1.2
Inrush Duration (μs)	520
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50Hz
Max. Luminaires per 16A C Breaker	133
Max. Luminaires per 16A B Breaker	66
Lifetime data	
Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Physical data	
Nominal Product Length (mm)	78
Nominal Product Diameter (mm)	45
Weight (kg)	0.045
TT GIGHT (Ng)	U.UTU




Pac		

Single packaging type	Carton
Product EAN number	5410288294933
Packaging single length / height (cm)	9.5
Packaging single width (cm)	5.0
Packaging single depth (cm)	5.0
DUN14 (outer)	15410288294930
Units per outer package	6
Packaging outer length / height (cm)	15.8
Packaging outer width (cm)	10.7
Packaging outer depth (cm)	10.5

#### Safety data

Optimal operating condition (°C)	-10-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

#### **PHOTOMETRY**



### **TECHNICAL DRAWINGS**





