



SERENE 1031C-L3106B-02 Reading Wall Bracket SERENE Slim LED SMD 6W 732lm CRI80 3000K USB A-USB C Black

Exo Lighting presents its SERENE reader wall lamp. Made of steel and nuanced methacrylate. Available in LED technology SMD USB right, USB left, Slim and Slim right. It has a color temperature of 3000K, ideal for illuminating rooms. Its USB technology will allow you to charge any device such as mobile or tablet. You can choose between its white or black finishes.



GENERAL DATA

| | |
|-------------------|----------------------|
| Category | Surface |
| Family | Serene |
| Finish | [02] Black |
| Location | Indoor |
| Installation | Wall |
| Body material | Steel |
| Diffuser material | Frosted methacrylate |
| EAN | 8433264353698 |

LIGHT SOURCES AND BEAMS

| | |
|-------------------|------------------------------|
| Sources | LED SMD 6W 732lm 3000K CRI80 |
| Total flux | 434 lm |
| Energy efficiency | E (3000K) |
| Beam | Diffuse |

TECHNICAL DATA

| | |
|----------------------------|---|
| Dimensions | Height x Width x Depth (mm): 80 x 200 x 120 |
| IP | IP20 |
| Protection class | Class I |
| Frequency | 50/60 Hz |
| Input voltage | 220-240V AC V |
| Output current | 300 mA |
| Power factor | 0.8 |
| Auxiliary equipment brand | Kegu |
| Charger connector type | USB A-USB C |
| USB ports charging devices | (2) x 5V 2.1mA |
| Power switches | 1 |
| Lifetime | 30.000 h |
| LED lifetime L | 70 |
| LED lifetime B | 50 |
| Weight | 0.702 Kg |
| Rotation angle | 350.0 ° |

SERENE

1031C-L3106B-02 Reading Wall Bracket SERENE Slim LED SMD 6W 732lm CRI80
3000K USB A-USB C Black

PRODUCTS OF THE SAME FAMILY



Serene USB
Left

Serene USB Right