

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Apete

VK/04619/PE/B-CB/W


LED Pendant Linear Light. 3000K. 40W. 5.756lm. CRI>90. IP20, Black+chrome black reflector




IP20



Dimensions



Gallery



LED Pendant Linear Light

Apete



Apete





Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	40W
Voltage	220-240V
Extra	Included 1m hanging accessories & screws
Fitting	LED Pendant
Type	Light
Safety class	
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Driver	Boke Dali
Working temperature	< 45°C
PAGE	58 Decorative 2024
NICKNAME	Apete

Physical Specifications	
Color	Black+chrome black reflector
Material	Aluminium
Width	3.4cm
Length	150cm
Height	7.6cm
Width (inner box)	5cm
Length (inner box)	11cm
Height (inner box)	156.5cm

Illumination Data	
Lumen	5.756lm
Beam angle	38°
Lighting direction	

Packing Info

Pcs/carton	1pc
------------	-----

Certification & Warranty

Guarantee	5 years
-----------	---------

Energy Label

The image shows an energy label for a VK Leading Light. At the top left is the EU Energy logo. Below it, the text reads "VK LEADING LIGHT" and "VK/04619/PE/B-CB/W". A vertical scale of energy efficiency classes from A to G is shown, with class D highlighted in a black arrow pointing to the right. Below the scale, the energy consumption is listed as "40 kWh/1000h". A QR code is located at the bottom right of the label, with the date "2019/2015" printed vertically next to it.