

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Baro

VK/04620/PE/W/W


Pendant light LED. 3000K. 620lm. 5W. 24° CRI>90. IP20, white



IP20



Dimensions



Gallery



Pendant Lights Led

Baro





Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	5W
Voltage	220-240V
Lampholder	
Fitting	LED Pendant
Type	Light
Safety class	
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Cable Length	1000mm
Working temperature	< 45°C
PAGE	98 Decorative 2024
NICKNAME	Baro

Physical Specifications	
Color	White
Material	Aluminium
Width	ø4cm
Length	60cm
Width (inner box)	8cm
Length (inner box)	76.3cm
Height (inner box)	7.6cm

Illumination Data	
Lumen	620lm
Beam angle	24°
Lighting direction	

Packing Info

Pcs/carton	1pc
------------	-----

Certification & Warranty

Guarantee	5 years
-----------	---------

Energy Label

The image shows an energy label for a VK Leading Light. At the top left is the European Union flag and the word "ENERGY" with a lightning bolt icon. Below this, it says "VK LEADING LIGHT" and "VK/04620/PE/W/W". The label features a vertical scale of energy efficiency classes from A (green) at the top to G (red) at the bottom. A black arrow points to class E. Below the scale, it indicates a consumption of "5 kWh/1000h". There is a QR code and the date "2019/2015" on the right side of the label.