

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr



Mute

VK/04561/45/BL/W/DA



MUTE, Acoustic Led Lights Up/Down. 3000K. 22W. 3.200lm (Up 1.015lm, Down 2.175lm). Up 130°/Down 65°, CRI>80. IP20, Dimmable DALI, Blue

IP20 DALI   CE

Dimensions	Gallery	Downloads
	 	  

Technical Specifications	
Kelvin	3000K
Power	22W
Voltage	220-240V
Extra	Soundproof LED lighting
Fitting	Ceiling-Pendant
Type	Acoustic Led Lights Up/Down
Safety class	
Light source	Samsung 2835
IP Rating	IP20
CRI	CRI>80
Dimmable	
Lifetime	50.000hrs
Driver	BOKE Dali (included)
Cable Length	1.5m
Working temperature	-20°C - 40°C
PAGE	548 Technical 2024
NICKNAME	Mute

Physical Specifications	
Cable	Black fabric
Color	Blue
Material	Polyester Fiber Acoustic + Aluminium Alloy
Width	36cm
Length	61cm
Height	6.4cm
Net weight of product (kg)	3
Gross weight with inner box (kg)	4
Width (inner box)	55.5cm
Length (inner box)	67cm
Height (inner box)	10.5cm

Illumination Data	
Lumen	3.200lm (Up 1.015lm, Down 2.175lm)
Beam angle	Up 130°/Down 65°
Lighting direction	

Packing Info	
Pcs/carton	1pc

Certification & Warranty	
Guarantee	3 years

Energy Label

ENERGY

VK LEADING LIGHT

VK/04561/45/BL/W/DA

A

B

C

D

E

F

G

22

kWh/1000h



2019/2015