


MITRA 208A-L02X1K-03

Recessed floor MITRA IP68 LED SMD 0.69W CRI80 Grey



Mitra ground recessed, made of aluminum with a degree of protection IP68, available in two amber and standard versions. This luminaire works without recharging 16 hours in environments with severe temperatures -25° +60 °C. These downlights are suitable for installations on surfaces with a saline atmosphere.

GENERAL DATA

Category	Recessed
Family	Mitra
Finish	1031 Grey
Location	Outdoor
Installation	Floor
Body material	Aluminum
Diffuser material	Transparent polycarbonate
Reflector material	Polycarbonate
ETIM class	EC000481
EAN	8433264103903

LIGHT SOURCES AND BEAMS

Sources	LED SMD 0.693W max. CRI80
Total flux	0 lm

TECHNICAL DATA

Dimensions	Width x Height x Depth (mm): 148 x 148 x 50
IP	IP68
IK	10
Dinamic pressure	19,000.0 Kg
Protection class	Class III
Input voltage	3.7V DC V
Output current	10 mA
Battery charge time	3.0 h
Battery autonomy	12.0 h
Operating temperature range	-40 - 70 °C
Lifetime	50,000 h
LED lifetime L	80
LED lifetime B	20
Weight	1.0 Kg
ECORAE category I	LED-B

NOTES

Loading time: 3/8h
Full load duration: 16h
Sensor level: 150/350 lux
Thermal amplitude: -25° +60 °C
Luminaire suitable for installation in environments with saline atmosphere

MITRA 208A-L02X1K-03

Recessed floor MITRA IP68 LED SMD 0.69W CRI80 Grey

PRODUCTS OF THE SAME FAMILY



Mitra Steady