

SPARK

294D-G05X1A-04



Spotlights / Base Spotlight / Spike tilt SPARK Grid IP65 E27 75W Anthracite

Cristher

La familia de proyectores Spark está fabricada de aluminio y cuenta con IP54 y IP65 para instalaciones sobre la pared, suelo y techo. Está disponible en varias temperaturas de color 3000K y 4000K y su ángulo de rotación máx. es 355°, incluye la rejilla antideslumbrante. Esta luminaria está hecha para iluminar las zonas exteriores.

GENERAL DATA

Category	Spotlights
Family	Spark
Finish	[04] Anthracite
Location	Outdoor
Installation	Ceiling, Floor, Wall
Body material	Aluminum
Diffuser material	Transparent glass
ETIM class	EC001744
EAN	8435256510195

LIGHT SOURCES

PAR30	
Light source power	75 W
Lamp included	No

LIGHT BEAMS


Beam	Directa
------	---------

TECHNICAL DATA

Dimensions	Length x Height x Width (mm): 125 x 390 x 180
IP	IP65
IP2	IP44
Corrosion resistance	Yes
Protection class	Class I
Frequency	50/60 Hz
Input voltage	110-240V AC V
Auxiliary gear	Without equipment, not needed
Glow wire temperature	850.0 °C
Weight	1.6 Kg
Cable outlets	1
Lead wire length	2,500.0 mm
Tilt angle	90.0 °
Rotation angle	355.0 °
ECORAE category I	CAT-B
ECORAE I	0.5
Flammable surfaces	Yes

NOTES

With anti-dazzle grille Included.



SPARK

294D-G05X1A-04



Spotlights / Base Spotlight / Spike tilt SPARK Grid IP65 E27 75W Anthracite

Cristher



RECOMMENDED ACCESSORIES

632C-L0506B-01	Input voltage	110-240V AC
Lamp LED FILAMENT E27 LED Bulb 6W 800lm(800lm) CRI80 2700K 360°	Frequency	50/60
	Wattage (w)	6.0
	IP	IP20
	Protection class	Class I

632C-L0506B-02	Input voltage	110-240V AC
Lamp LED FILAMENT E27 LED Bulb 6W 800lm(800lm) 4000K 360°	Frequency	50/60
	Wattage (w)	6.0
	IP	IP20
	Protection class	Class I

