


# UTU MINI

338A-L02X1K-29 Recessed floor UTU MINI IP68 LED SMD 0.33W CRI80 Transparent

Family of solar wall lights Utu mini is made of polycarbonate with IP68, in a square shape, available in two versions: LED SMD and LED SMD AMBER. It is installed on the ground. It is recommended to illuminate the passage areas of large outdoor surfaces.



## GENERAL DATA

Category	Recessed
Family	Utu mini
Finish	[29] Transparent
Location	Outdoor
Installation	Floor
Body material	Polycarbonate
Diffuser material	Transparent polycarbonate
ETIM class	EC000347
EAN	8435256541571

## LIGHT SOURCES AND BEAMS

Sources	LED SMD 0,325W CRI80
Total flux	0 lm
Beam	Diffuse

## TECHNICAL DATA

Dimensions	Width x Height x Depth (mm): 118 x 118 x 61
IP	IP68
IK	10
Dinamic pressure	3,500.0 Kg
Protection class	Class III
Input voltage	3.15V DC V
Output current	7 mA
Battery charge time	3.0 h
Battery autonomy	12.0 h
Surface temperature	-40.0 °C
Operating temperature range	70 °C
Lifetime	50,000 h
LED lifetime L	80
LED lifetime B	20
Weight	0.82 Kg
ECORAE category I	LED-B

## NOTES

Loading time: 3/8h
Full load duration: 18h
Sensor level: 150/350 lux
Thermal amplitude: -25° +60 °C
Luminaire suitable for installation in environments with saline atmosphere

# UTU MINI 338A-L02X1K-29 Recessed floor UTU MINI IP68 LED SMD 0.33W CRI80 Transparent

**PRODUCTS OF THE SAME FAMILY**

---



Utu Mini Ambar