


UTU ROUND

339A-L07X1K-29 Recessed floor UTU ROUND IP68 LED SMD Ambar 0.33W CRI80 Transparent

Family of solar wall lights Utu round is made of polycarbonate with IP68, available in two versions: LED SMD and LED SMD AMBER. It is installed on the ground. It is recommended to illuminate the passage areas of large outdoor surfaces.



GENERAL DATA

Category	Recessed
Family	Utu round
Finish	[2g] Transparent
Location	Outdoor
Installation	Floor
Body material	Polycarbonate
Diffuser material	Transparent polycarbonate
ETIM class	EC000347
EAN	8433264104306

LIGHT SOURCES AND BEAMS

Sources	LED SMD AMBAR 0.325W CRI80
Total flux	0 lm
Beam	Diffuse

TECHNICAL DATA

Dimensions	Maximum height x Width x Depth (mm): 118 x 118 x 61
IP	IP68
IK	10
Dinamic pressure	3,500.0 Kg
Protection class	Class III
Input voltage	3.15V DC V
Output current	7 mA
Battery charge time	3.0 h
Battery autonomy	12.0 h
Operating temperature range	-40 - 70 °C
Lifetime	50,000 h
LED lifetime L	80
LED lifetime B	20
Weight	880.0 Kg
ECORAE category I	LED-B

NOTES

Loading time: 3/8h
Full load duration: 18h
Sensor level: 150/350 lux
Thermal amplitude: -25° +60 °C
Luminaire suitable for installation in environments with saline atmosphere

UTU ROUND

339A-L07X1K-29 Recessed floor UTU ROUND IP68 LED SMD Ambar 0.33W
CRI80 Transparent

PRODUCTS OF THE SAME FAMILY



Utu Round