



LISBOA 402D-L0175B-02 Surface Mounted Spotlight LISBOA IP66 LED COB 75W 9900lm CRI85
3000K 40° 190° Black



Familia de proyectores Lisboa está fabricada en aluminio y cuenta con IP66. Está disponible en tres diferentes tamaños para iluminar las zonas ajardinadas del exterior. Su temperatura de color es de 3000K, incluyen la piqueta y el tratamiento de protección contra la corrosión.

GENERAL DATA

| | |
|-------------------|----------------------|
| Category | Spotlights |
| Family | Lisboa |
| Finish | [02] Black |
| Location | Outdoor |
| Installation | Ceiling, Floor, Wall |
| Body material | Aluminum |
| Diffuser material | Transparent glass |
| ETIM class | EC001744 |
| EAN | 8435256541250 |

LIGHT SOURCES AND BEAMS

| | |
|-------------------|-------------------------------------|
| Sources | LED COB 75W max. 9900lm 3000K CRI85 |
| Energy efficiency | D |
| Beam | 40° - Direct symmetric |

TECHNICAL DATA

| | |
|-----------------------|----------------------------------------------|
| Dimensions | Height x Width x Length (mm): 300 x 234 x 61 |
| IP | IP66 |
| IK | 10 |
| Protection class | Class I |
| Frequency | 50/60 Hz |
| Input voltage | 220-240V AC V |
| Auxiliary gear | Electronic |
| Glow wire temperature | 850.0 °C |
| Lifetime | 50,000 h |
| LED lifetime L | 80 |
| LED lifetime B | 10 |
| Weight | 5.2 Kg |
| Cable outlets | 1 |
| Lead wire length | 2,000.0 mm |
| Tilt angle | 190.0 ° |
| ECORAE category I | LED-B |
| ECORAE I | 0.5 |
| Flammable surfaces | Yes |
| Electric screwdriver | Yes |

NOTES

Available in beams (40° - 60° - 70°)

* Con un tratamiento de protección contra la corrosión

LISBOA 402D-L0175B-02 Surface Mounted Spotlight LISBOA IP66 LED COB 75W 9900lm CRI85
3000K 40° 190° Black

COMPLEMENTARY IMAGES



PRODUCTS OF THE SAME FAMILY



Lisboa M



Lisboa S