

## Ago Applique

<b>IP66 IK 07 2J xx5</b> CE UK ER	LED			W    LM    REAL LM	COL.    CODE *	
	5	600	497			

\* Complete the CODE    ○ OPTIC    D | Diff.    S | 25°    M | 40°    L | 65°    □ LED COLOUR    N | 4000K    3 | 3000K    2 | 2700K    1 | 2200K

Versione LL126203: alluminio verniciato | Version LL126203: painted aluminium | Version LL126203: aluminium paint

## Ago Applique U&D

<b>IP66 IK 07 2J xx5</b> CE UK ER	LED			W    LM    REAL LM	COL.    CODE *	
	10	1200	996			

\* Complete the CODE    ○ OPTIC    D | Diff.    S | 25°    M | 40°    L | 65°    □ LED COLOUR    N | 4000K    3 | 3000K    2 | 2700K    1 | 2200K

Versione LL126207: alluminio verniciato | Version LL126207: painted aluminium | Version LL126207: aluminium paint


## Accessori | Accessories | Accessoires

### Base Ago Applique verniciata

Painted Ago Applique base

Base Ago Applique paint

Col.	Code
	LB1262004
	LB1262005



### Bus DALI

Variatore universale comandabile con segnale DALI.  
 Dimmerazione a Taglio di Fase discendente (a fine fase)  
 IGBT Trailing-Edge.

Col.	Code
-	LB1070110

#### Bus DALI

Universal dimmer controlled by DALI signal. Descending Phase Cutting dimming (at the end of the phase) IGBT Trailing-Edge.

#### Bus DALI

Variateur universel commandé par un signal DALI. Phase descendante Gradation par coupure (à la fin de la phase) IGBT Trailing-Edge.

