


# BARLIA 540A-L0102B-30

Wall recessed BARLIA IP54 LED SMD AC 2W 150lm CRI80 3000K

Stainless steel

Empotrable de pared Barlia, fabricado de acero inoxidable con un grado de protección IP54, disponible en temperatura de color de 3000K. La profundidad de empotramiento es de 8cm. Son luminarias diseñadas para iluminar las zonas de paso y residenciales en los espacios exteriores.



## GENERAL DATA

Category	Recessed
Family	Barlia
Finish	[30] Stainless steel
Location	Outdoor
Installation	Wall
Body material	Aluminum
Diffuser material	Opal polycarbonate
Frame material	Inox aisi 304
ETIM class	EC000481
EAN	8435258612385

## LIGHT SOURCES AND BEAMS

Sources	LED SMD AC 2W max. 150lm 3000K CRI80
Total flux	56 lm
Energy efficiency	G
Beam	Direct symmetric

## TECHNICAL DATA

Dimensions	Length x Height x Depth (mm): 170 x 70 x 80
IP	IP54
IK	08
Protection class	Class I
Frequency	50/60 Hz
Input voltage	220-240V AC V
Lifetime	30,000 h
LED lifetime L	80
LED lifetime B	50
Weight	0.4 Kg
Cable outlets	1
Lead wire length	100.0 mm
Cut hole box included	Yes
Cut hole dimensions	Length x Height x Depth (mm): 159 x 57 x 78
ECORAAE category I	LED-A
ECORAAE I	0.5
Periodic maintenance	Yes
Flammable surfaces	Yes