


BELL 586A-G05X1A-01

Suspended Lamp BELL E27 42W White



Bell is a pendant white, made of aluminum with 27cm diameter. It is modern in style, so it fits perfectly to any residential house.

GENERAL DATA

Category	Pendant
Family	Bell
Finish	[01] White
Location	Indoor
Installation	Ceiling
Body material	Aluminum
ETIM class	EC001743
EAN	8435258612828

LIGHT SOURCES AND BEAMS

Sources	E27 LED Bulb/TC-TSE/HAL 42W max.
Energy efficiency	A++, A+, A, B, C, D, E
Lamp included	No
Beam	Direct symmetric

TECHNICAL DATA

Dimensions	Maximum height x Width (mm): 1760 x 270
IP	IP20
Protection class	Class II
Frequency	50/60 Hz
Input voltage	110-240V AC V
Weight	1.7 Kg
ECORAE category I	CAT-B

BELL 586A-G05X1A-01

Suspended Lamp BELL E27 42W White

RECOMMENDED ACCESSORIES

		<p>632F-L0504B-01 Lamp LED FILAMENT E27 LED Bulb 4W 470lm CRI80 2700K 360°</p>	<table border="1"> <tbody> <tr> <td>Input voltage</td> <td>220-240V AC</td> </tr> <tr> <td>Frequency</td> <td>50/60</td> </tr> <tr> <td>Wattage (W)</td> <td>4.0</td> </tr> <tr> <td>IP</td> <td>IP20</td> </tr> <tr> <td>Protection class</td> <td>Class I</td> </tr> </tbody> </table>	Input voltage	220-240V AC	Frequency	50/60	Wattage (W)	4.0	IP	IP20	Protection class	Class I
Input voltage	220-240V AC												
Frequency	50/60												
Wattage (W)	4.0												
IP	IP20												
Protection class	Class I												
		<p>632C-L0506B-01 Lamp LED FILAMENT E27 LED Bulb 6W 800lm CRI80 2700K 360°</p>	<table border="1"> <tbody> <tr> <td>Input voltage</td> <td>110-240V AC</td> </tr> <tr> <td>Frequency</td> <td>50/60</td> </tr> <tr> <td>Wattage (W)</td> <td>6.0</td> </tr> <tr> <td>IP</td> <td>IP20</td> </tr> <tr> <td>Protection class</td> <td>Class I</td> </tr> </tbody> </table>	Input voltage	110-240V AC	Frequency	50/60	Wattage (W)	6.0	IP	IP20	Protection class	Class I
Input voltage	110-240V AC												
Frequency	50/60												
Wattage (W)	6.0												
IP	IP20												
Protection class	Class I												
		<p>632G-L0504B-01 Lamp LED FILAMENT E27 LED Bulb 4W 470lm CRI80 2700K 360°</p>	<table border="1"> <tbody> <tr> <td>Input voltage</td> <td>220-240V AC</td> </tr> <tr> <td>Frequency</td> <td>50/60</td> </tr> <tr> <td>Wattage (W)</td> <td>4.0</td> </tr> <tr> <td>IP</td> <td>IP20</td> </tr> <tr> <td>Protection class</td> <td>Class I</td> </tr> </tbody> </table>	Input voltage	220-240V AC	Frequency	50/60	Wattage (W)	4.0	IP	IP20	Protection class	Class I
Input voltage	220-240V AC												
Frequency	50/60												
Wattage (W)	4.0												
IP	IP20												
Protection class	Class I												