



# KARI 745C-L0301B-39 Wall recessed KARI IP30 LED SMD 1W 27lm CRI80 5000K Anodized aluminum



KARI is a range of LED recessed made of aluminum for signaling corridors, stairways and other spaces. The KARI luminaire stands out for its multitude of shapes and finishes for different environments and has been designed from different temperatures warm color and cold.

## GENERAL DATA

Category	Recessed
Family	Kari
Finish	[39] Anodized aluminum
Location	Indoor
Installation	Wall
Body material	Steel
Diffuser material	Transparent glass
Frame material	Aluminum
Reflector material	Stepped aluminum
ETIM class	EC000481
EAN	8433264011802

## LIGHT SOURCES AND BEAMS

Sources	LED SMD 1W max. 27lm 5000K CRI80
Energy efficiency	A+, A
Beam	Direct asymmetric

## TECHNICAL DATA

Dimensions	Height x Width (mm): 78 x 78
IP	IP30
Protection class	Class II
Frequency	50/60 Hz
Input voltage	220-240V AC V
Auxiliary gear	Driver integrado
Lifetime	35,000 h
LED lifetime L	80
LED lifetime B	20
Weight	0.3 Kg
Cut hole dimensions	Length x Width (mm): 68 x 64
ECORAAE category I	LED-A