



NIX 780E-G42X1B-48

Recessed ceiling NIX GU10 50W 30° Niquel matt



NIX is a family of recessed LED discreet interior spaces that has been made from many applications and in two versions, one fixed and one steerable. NIX has been developed from two designs, one square and circular aluminum construction make it a functional and efficient luminaire for LED Indoor lighting.

GENERAL DATA

Category	Recessed
Family	Nix
Finish	[48] Niquel matt
Location	Indoor
Installation	Ceilling
Body material	Aluminum
Frame material	Aluminum
ETIM class	EC001744
EAN	8435258614259

LIGHT SOURCES AND BEAMS

Sources	GU10 QPAR-16 50W max.
Lamp included	No
Beam	Direct symmetric

TECHNICAL DATA

Dimensions	Height x Width x Length (mm): 82 x 82 x 55
IP	IP20
Protection class	Class II
Frequency	50/60 Hz
Input voltage	110-240V AC V
Weight	0.075 Kg
Tilt angle	30.0 °
Cut hole dimensions	Diameter (mm): 75
ECORAE category I	CAT-A

NIX 780E-G42X1B-48

Recessed ceiling NIX GU10 50W 30° Niquel matt

RECOMMENDED ACCESSORIES

		B02T-X3370D-02 Power supplies ACCESORIOS Black	<table border="1"> <tr><td>Input voltage</td><td>220-240V AC</td></tr> <tr><td>Frequency</td><td>50/60</td></tr> <tr><td>Wattage (W)</td><td>50.0</td></tr> <tr><td>IP</td><td>IP20</td></tr> </table>	Input voltage	220-240V AC	Frequency	50/60	Wattage (W)	50.0	IP	IP20				
Input voltage	220-240V AC														
Frequency	50/60														
Wattage (W)	50.0														
IP	IP20														
		578A-L2105A-02 Lamp LED PRO GU10 LED Bulb 4.50W 300lm CRI80 4000K 38° White	<table border="1"> <tr><td>Input voltage</td><td>110-240V AC</td></tr> <tr><td>Frequency</td><td>50/60</td></tr> <tr><td>Wattage (W)</td><td>4.5</td></tr> <tr><td>IP</td><td>IP20</td></tr> <tr><td>Protection class</td><td>Class I</td></tr> </table>	Input voltage	110-240V AC	Frequency	50/60	Wattage (W)	4.5	IP	IP20	Protection class	Class I		
Input voltage	110-240V AC														
Frequency	50/60														
Wattage (W)	4.5														
IP	IP20														
Protection class	Class I														
		578A-L2104A-01 Lamp LED PRO GU10 3.50W 36° White	<table border="1"> <tr><td>Input voltage</td><td>110-240V AC</td></tr> <tr><td>Frequency</td><td>50/60</td></tr> <tr><td>Wattage (W)</td><td>3.5</td></tr> <tr><td>IP</td><td>IP20</td></tr> <tr><td>Protection class</td><td>Class I</td></tr> </table>	Input voltage	110-240V AC	Frequency	50/60	Wattage (W)	3.5	IP	IP20	Protection class	Class I		
Input voltage	110-240V AC														
Frequency	50/60														
Wattage (W)	3.5														
IP	IP20														
Protection class	Class I														
		729A-L33R1B-00 Recessed ceiling ACCESORIOS 1- 10V,Push LED COB 8W 803lm CRI85 4000K 40°	<table border="1"> <tr><td>Input voltage</td><td>110-240V AC</td></tr> <tr><td>Frequency</td><td>50/60</td></tr> <tr><td>Wattage (W)</td><td>8.0</td></tr> <tr><td>IP</td><td>IP20</td></tr> <tr><td>Protection class</td><td>Class II</td></tr> <tr><td>Dimmable</td><td>1-10V, Push</td></tr> </table>	Input voltage	110-240V AC	Frequency	50/60	Wattage (W)	8.0	IP	IP20	Protection class	Class II	Dimmable	1-10V, Push
Input voltage	110-240V AC														
Frequency	50/60														
Wattage (W)	8.0														
IP	IP20														
Protection class	Class II														
Dimmable	1-10V, Push														
		578A-L2104A-02 Lamp LED PRO GU10 3.50W 36° White	<table border="1"> <tr><td>Input voltage</td><td>110-240V AC</td></tr> <tr><td>Frequency</td><td>50/60</td></tr> <tr><td>IP</td><td>IP20</td></tr> <tr><td>Protection class</td><td>Class I</td></tr> </table>	Input voltage	110-240V AC	Frequency	50/60	IP	IP20	Protection class	Class I				
Input voltage	110-240V AC														
Frequency	50/60														
IP	IP20														
Protection class	Class I														
		729A-L31R1B-00 Recessed ceiling ACCESORIOS 1- 10V,Push LED COB 8W 766lm CRI85 3000K 40°	<table border="1"> <tr><td>Input voltage</td><td>110-240V AC</td></tr> <tr><td>Frequency</td><td>50/60</td></tr> <tr><td>Wattage (W)</td><td>8.0</td></tr> <tr><td>IP</td><td>IP20</td></tr> <tr><td>Protection class</td><td>Class II</td></tr> <tr><td>Dimmable</td><td>1-10V, Push</td></tr> </table>	Input voltage	110-240V AC	Frequency	50/60	Wattage (W)	8.0	IP	IP20	Protection class	Class II	Dimmable	1-10V, Push
Input voltage	110-240V AC														
Frequency	50/60														
Wattage (W)	8.0														
IP	IP20														
Protection class	Class II														
Dimmable	1-10V, Push														
		729A-L3108B-00 Recessed ceiling ACCESORIOS LED COB 8W 766lm CRI85 3000K 40°	<table border="1"> <tr><td>Input voltage</td><td>220-240V AC</td></tr> <tr><td>Frequency</td><td>50/60</td></tr> <tr><td>Wattage (W)</td><td>8.0</td></tr> <tr><td>IP</td><td>IP20</td></tr> <tr><td>Protection class</td><td>Class II</td></tr> </table>	Input voltage	220-240V AC	Frequency	50/60	Wattage (W)	8.0	IP	IP20	Protection class	Class II		
Input voltage	220-240V AC														
Frequency	50/60														
Wattage (W)	8.0														
IP	IP20														
Protection class	Class II														

NIX 780E-G42X1B-48

Recessed ceiling NIX GU10 50W 30° Niquel matt



729A-L3308B-00
 Recessed ceiling ACCESORIOS
 LED COB 8W 803lm CRI85 4000K
 40°

Input voltage	220-240V AC
Frequency	50/60
Wattage (W)	8.0
IP	IP20
Protection class	Class II

NIX 780E-G42X1B-48

Recessed ceiling NIX GU10 50W 30° Niquel matt

PRODUCTS OF THE SAME FAMILY



Nix Round



Nix Round 2



Nix Round LED



Nix Round Tilt 2

Nix Round Tilt LED



Nix Square



Nix Square 2



Nix Square LED



Nix Square Tilt



Nix Square Tilt 2



Nix Square Tilt LED