


BUIS 805C-L3335A-01

Surface Mounted BUIS IP54 LED COB 32W 3430lm CRI80 4000K 70° White



Surface Downlight LED BUIS has been manufactured partrir three sizes and powers that favor their flow of light. This LED downlight features high IP protection making it suitable for lighting fixture bathrooms, kitchens and porches and canopies above all, or interior lighting epacios requiring sober and discreet.

GENERAL DATA

Category	Surface
Family	Buis
Finish	[01] White
Location	Indoor
Installation	Ceilling
Body material	Aluminum
Diffuser material	Clear transparent glass
Reflector material	Faceted aluminum
ETIM class	EC0028g2
EAN	8433264071691

LIGHT SOURCES AND BEAMS


Sources	LED COB 32W max. 3430lm 4000K CRI80
Energy efficiency	A+
Beam	70° - Direct symmetric

TECHNICAL DATA

Dimensions	Height x Diameter (mm): 120 x 160
IP	IP54
Protection class	Class I
Frequency	50/60 Hz
Input voltage	110-240V AC V
Power factor	0.9
Auxiliary gear	Electronic
Lifetime	40,000 h
LED lifetime L	80
LED lifetime B	20
Weight	1.3 Kg
ECORAE category I	LED-B



PHOTOMETRIC DATA



BUIS

805C-L3335A-01 Surface Mounted BUIS IP54 LED COB 32W 3430lm CRI80 4000K 70° White

PRODUCTS OF THE SAME FAMILY



Buis M



Buis S