


SIGMA 809A-L38RDB-01

Suspended Lamp SIGMA Dali LED SMD 44W 5404lm CRI90 2700K 48° White

The SIGMA family is the discretion and slenderness LED luminaire made with a section of only 32x44 mm and two lengths to efficiently illuminate a work surface, a counter hotel, an office desk. This range has been manufactured from shaped ceiling lamps and recessed version. The SIGMA lights have a possibility of regulation that make them ideal for environments such as homes, catering or hospitality environments.



GENERAL DATA

| | |
|--------------------|-------------------------|
| Category | Pendant |
| Family | Sigma |
| Finish | [01] White |
| Location | Indoor |
| Installation | Ceiling |
| Body material | Aluminum, Polycarbonate |
| Frame material | Aluminum |
| Reflector material | Metallic ABS |
| ETIM class | EC001743 |
| EAN | 8433264123826 |


LIGHT SOURCES AND BEAMS

| | |
|-------------------|--------------------------------|
| Sources | LED SMD 44W 5404lm 2700K CRI90 |
| Total flux | 4543 lm |
| Energy efficiency | E (2700K) |
| Beam | 48° - Direct symmetric |

TECHNICAL DATA

| | |
|-------------------|--|
| Dimensions | Height x Width x Length (mm): 40 x 32 x 1117 |
| IP | IP20 |
| Protection class | Class I |
| Frequency | 50/60 Hz |
| Dimmable | Dali |
| Input voltage | 220-240V AC V |
| Auxiliary gear | Electronic |
| UGR | 19 |
| Lifetime | 60,000 h |
| LED lifetime L | 80 |
| LED lifetime B | 20 |
| Weight | 1.8 Kg |
| Lead wire length | 1,000.0 mm |
| ECORAE category I | LED-B |

PHOTOMETRIC DATA



SIGMA 809A-L38RDB-01 Suspended Lamp SIGMA Dali LED SMD 44W 5404lm CRI90 2700K 48°
White

SIGMA 809A-L38RDB-01 Suspended Lamp SIGMA Dali LED SMD 44W 5404lm CRI90 2700K 48°
White

PRODUCTS OF THE SAME FAMILY



Sigma L Mini-Trim



Sigma L Trimless



Sigma M Mini-Trim



Sigma M Trimless



Sigma S Mini-Trim



Sigma S Trimless



Sigma XXL