

SIGMA 809E-L3325B-03 Recessed ceiling SIGMA LED SMD 25W 2655lm CRI80 4000K 48° Grey

The SIGMA family is the discretion and slenderness LED luminaire made with a section of only 32x44 mm and two lengths to efficiently illuminate a work surface, a counter hotel, an office desk. This range has been manufactured from shaped ceiling lamps and recessed version. The SIGMA lights have a possibility of regulation that make them ideal for environments such as homes, catering or hospitality environments.



GENERAL DATA

Category	Recessed
Family	Sigma
Finish	[03] Grey
Location	Indoor
Installation	Ceiling
Body material	Aluminum, Polycarbonate
Frame material	Aluminum
Reflector material	Metallic ABS
ETIM class	EC000282
EAN	8433264073336


LIGHT SOURCES AND BEAMS

Sources	LED SMD 25W max. 2655lm 4000K CRI80
Energy efficiency	E
Beam	48° - Direct symmetric


TECHNICAL DATA

Dimensions	Height x Width x Length (mm): 42 x 42 x 650
IP	IP20
Protection class	Class II
Frequency	50/60 Hz
Input voltage	220-240V AC V
Output current	700 mA
Power factor	0.95
Auxiliary gear	Electronic
Alternative auxiliary equipment	1-10V CONV.JUS110P SIGMA + 60€ PVP
UGR	19
Lifetime	60.000 h
LED lifetime L	80
LED lifetime B	20
Weight	0.69 Kg
Cut hole dimensions	Length x Width x Depth (mm): 643 x 34 x 42
ECORAE category I	LED-A

PHOTOMETRIC DATA



SIGMA 809E-L3325B-03 Recessed ceiling SIGMA LED SMD 25W 2655lm CRI80 4000K 48° Grey



SIGMA 809E-L3325B-03 Recessed ceiling SIGMA LED SMD 25W 2655lm CRI80 4000K 48° Grey

COMPLEMENTARY IMAGES



PRODUCTS OF THE SAME FAMILY



Sigma L
Trimless



Sigma M Mini-
Trim



Sigma M
Trimless



Sigma S Mini-
Trim



Sigma S
Trimless



Sigma XL



Sigma XXL