


WALK 920G-L3112B-30 Recessed floor WALK IP67 LED SMD 12W 1740lm CRI80 3000K 100° 180°

Stainless steel

La familia Walk consiste en empotrables de suelo y proyectores de superficie fabricada de aluminio y cuenta con IP67. Está disponible en varias temperaturas de color y versión RGB, diferentes tipos de potencia max. hasta 80W. Gracias a su versatilidad es ideal para instalaciones en espacios exteriores.



GENERAL DATA

Category	Recessed
Family	Walk
Finish	[30] Stainless steel
Location	Outdoor
Installation	Floor
Body material	Aluminum
Diffuser material	Frosted glass
Frame material	Stainless steel
ETIM class	EC000758
EAN	8433264102975

LIGHT SOURCES AND BEAMS

Sources	LED SMD 12W max. 1740lm 3000K CRI80
Total flux	678 lm
Energy efficiency	D
Beam	100° - Directa

TECHNICAL DATA

Dimensions	Width x Width x Height (mm): 620 x 98 x 83
IP	IP67
IK	09
Static pressure	500.0 Kg
Dinamic pressure	500.0 Kg
Protection class	Class I
Frequency	50/60 Hz
Input voltage	220-240V AC V
Total wattage	13 W
Output current	500 mA
Power factor	0.9
Operating temperature range	20 - 50 °C
Lifetime	50.000 h
LED lifetime L	80
LED lifetime B	10
Cable outlets	1
Lead wire length	0.5 mm
Tilt angle	180.0 °
Cut hole box included	Yes
Cut hole dimensions	Length x Width x Depth (mm): 610 x 100 x 85
ECORAE category I	LED-B

WALK 920G-L3112B-30 Recessed floor WALK IP67 LED SMD 12W 1740lm CRI80 3000K 100° 180°
Stainless steel

COMPLEMENTARY IMAGES



PRODUCTS OF THE SAME FAMILY



Walk Flood
L1146



Walk Flood
L586



Walk Reces
L1180



Walk Reces
L620



Walk Reces Mat L1180