


# WALK 920G-L3312B-30 Recessed floor WALK IP67 LED SMD 12W 1840lm CRI80 4000K 100° 180°

Stainless steel

La familia Walk consiste en empotrables de suelo y proyectores de superficie fabricada de aluminio y cuenta con IP67. Está disponible en varias temperaturas de color y versión RGB, diferentes tipos de potencia max. hasta 80W. Gracias a su versatilidad es ideal para instalaciones en espacios exteriores.



## GENERAL DATA

Category	Recessed
Family	Walk
Finish	[30] Stainless steel
Location	Outdoor
Installation	Floor
Body material	Aluminum
Diffuser material	Frosted glass
Frame material	Stainless steel
ETIM class	EC000758
EAN	8433264102982

## LIGHT SOURCES AND BEAMS

Sources	LED SMD 12W max. 1840lm 4000K CRI80
Total flux	718 lm
Energy efficiency	C
Beam	100° - Directa

## TECHNICAL DATA

Dimensions	Width x Width x Height (mm): 620 x 98 x 83
IP	IP67
IK	09
Static pressure	500.0 Kg
Dinamic pressure	500.0 Kg
Protection class	Class I
Frequency	50/60 Hz
Input voltage	220-240V AC V
Total wattage	13 W
Output current	500 mA
Power factor	0.9
Operating temperature range	20 - 50 °C
Lifetime	50.000 h
LED lifetime L	80
LED lifetime B	10
Cable outlets	1
Lead wire length	0.5 mm
Tilt angle	180.0 °
Cut hole box included	Yes
Cut hole dimensions	Length x Width x Depth (mm): 610 x 100 x 85
ECORAE category I	LED-B

**WALK** 920G-L3312B-30 Recessed floor WALK IP67 LED SMD 12W 1840lm CRI80 4000K 100° 180°  
Stainless steel

COMPLEMENTARY IMAGES



PRODUCTS OF THE SAME FAMILY



Walk Flood  
L1146



Walk Flood  
L586



Walk Reces  
L1180



Walk Reces  
L620



Walk Reces Mat L1180