


# AURA 932B-L3333B-02 Column AURA IP65 LED SMD 33W 5240lm CRI80 4000K 120° 2000mm Black



The Aura family with its three beacon models at 260mm, 400mm and 680mm tall, together with its 2000m column mode variant allows to solve any need for exterior lighting. In addition to its differential design manufactured in aluminum, it has high technical characteristics and is available in oxide and black brown colors (other finishes to consult), both at 3000K and 4000K. It is suitable for illuminating any outer space in pedestrian areas, roads, terraces, or public and private gardens.

### GENERAL DATA

|                   |                      |
|-------------------|----------------------|
| Category          | Bollards and columns |
| Family            | Aura                 |
| Finish            | [02] Black           |
| Location          | Outdoor              |
| Installation      | Floor                |
| Body material     | Aluminum             |
| Diffuser material | Opal polycarbonate   |
| ETIM class        | EC000301             |
| EAN               | 8433264119959        |

### LIGHT SOURCES AND BEAMS

|                   |                                     |
|-------------------|-------------------------------------|
| Sources           | LED SMD 33W max. 5240lm 4000K CRI80 |
| Total flux        | 2340 lm                             |
| Energy efficiency | D                                   |
| Beams             | 120°                                |

### TECHNICAL DATA

|                              |   |
|------------------------------|---|
| Dimensions                   | Height x Width x Depth (mm): 2000 x 160 x 160 |
| IP                           | IP65  |
| IK                           | 08  |
| Protection class             | Class I                                       |
| Frequency                    | 50/60 Hz                                      |
| Input voltage                | 220-240V AC V                                 |
| Output current               | 350 mA  |
| Power factor                 | 0.9   |
| Auxiliary gear               | Electronic                                    |
| Auxiliary equipment brand    | TCI   |
| Operating temperature range  | -20 - 50 °C                                   |
| Lifetime                     | 50.000 h                                      |
| LED lifetime L               | 80  |
| LED lifetime B               | 10  |
| Weight                       | 16.8 Kg                                       |
| Cable outlets                | 1   |
| ECORAE category I            | LED-C   |
| Anchorage included           | Yes   |
| Post included                | Yes   |
| Post with inspection chamber | Yes   |
| Photobiological risk group   | RGo   |

# AURA

932B-L3333B-02 Column AURA IP65 LED SMD 33W 5240lm CRI80 4000K 120° 2000mm Black

**PRODUCTS OF THE SAME FAMILY**

---



Aura L260



Aura L400



Aura L680