



CALYPSO2 979B-L3312A-01

Recessed ceiling CALYPSO2 IP44 LED SMD 12W 1200lm
CRI80 4000K 110° White



GENERAL DATA

Category	Recessed
Family	CALYPSO2
Finish	[o1] White
Location	Indoor
Installation	Ceiling
Body material	Aluminum
Diffuser material	Frosted methacrylate
Frame material	Aluminum
ETIM class	EC001744
EAN	8433264115678


LIGHT SOURCES AND BEAMS

Sources	LED SMD 12W max. 1200lm 4000K CRI80
Total flux	986 lm
Energy efficiency	F
Beam	110° - Direct symmetric

TECHNICAL DATA

Dimensions	Height x Diameter (mm): 40 x 120
IP	IP44
Protection class	Class II
Frequency	50/60 Hz
Input voltage	110-240V AC V
Output current	300 mA
Power factor	0.5
Auxiliary gear	Remote driver
Lifetime	40.000 h
LED lifetime L	70
LED lifetime B	20
Cut hole dimensions	Diameter (mm): 105
ECORAAE category I	LED-B

PHOTOMETRIC DATA



CALYPSO2 979B-L3312A-01

Recessed ceiling CALYPSO2 IP44 LED SMD 12W 1200lm
CRI80 4000K 110° White

PRODUCTS OF THE SAME FAMILY



Calypso2 L



Calypso2 S



Calypso2 XL