



# CALYPSO2 979C-L3324A-01

Recessed ceiling CALYPSO2 IP44 LED SMD 24W 2520lm  
CRI80 4000K 110° White



## GENERAL DATA

Category	Recessed
Family	CALYPSO2
Finish	[o1] White
Location	Indoor
Installation	Ceiling
Body material	Aluminum
Diffuser material	Frosted methacrylate
Frame material	Aluminum
ETIM class	EC001744
EAN	8433264115692


## LIGHT SOURCES AND BEAMS

Sources	LED SMD 24W max. 2520lm 4000K CRI80
Total flux	1960 lm
Energy efficiency	F
Beam	110° - Direct symmetric

## TECHNICAL DATA

Dimensions	Height x Diameter (mm): 40 x 170
IP	IP44
Protection class	Class II
Frequency	50/60 Hz
Input voltage	220-240V AC V
Output current	580 mA
Power factor	0.9
Auxiliary gear	Remote driver
Lifetime	40.000 h
LED lifetime L	70
LED lifetime B	20
Weight	1.3 Kg
Cut hole dimensions	Diameter (mm): 155
ECORAE category I	LED-B

## PHOTOMETRIC DATA



# CALYPSO2 979C-L3324A-01

Recessed ceiling CALYPSO2 IP44 LED SMD 24W 2520lm  
CRI80 4000K 110° White

## PRODUCTS OF THE SAME FAMILY

---



Calypso2 M



Calypso2 S



Calypso2 XL