


GIBSON 998A-L3306E-02 Surface Mounted Spotlight GIBSON IP65 LED SMD 6W 650lm CRI80 4000K 36° 150° Black

The Gibson family offers a surface and pinete solution that works at very low voltage (12V) to guarantee a safe installation against water or electric shock. Its robust and light design allows to swift the optical group, and together with the two potentities, optics and temperature offered, enable multiple lighting options. You need an external 12V transformer as our references B02E-X3330E-00 and B02E-X3375E-00. Ideal luminaire for patios, parks or gardens.



GENERAL DATA

Category	Spotlights
Family	Gibson
Finish	[02] Black
Location	Outdoor
Installation	Floor
Body material	Aluminum
EAN	8433264121037

LIGHT SOURCES AND BEAMS

Sources	LED SMD 6W max. 650lm 4000K CRI80
Total flux	475 lm
Energy efficiency	F
Beam	36°

TECHNICAL DATA

Dimensions	Diameter x Height x Depth (mm): 76 x 262 x 57.5
IP	IP65
Protection class	Class III
Frequency	50/60 Hz
Input voltage	12V DC V
Lifetime	50.000 h
LED lifetime L	70
LED lifetime B	50
Weight	0.35 Kg
Cable outlets	1
Lead wire length	500.0 mm
Tilt angle	150.0 °
Anchorage included	Yes

NOTES

IP connector included

GIBSON 998A-L3306E-02 Surface Mounted Spotlight GIBSON IP65 LED SMD 6W 650lm CRI80
4000K 36° 150° Black

RECOMMENDED ACCESSORIES



B02E-X3330E-00
Fuente alimentación 12V SKOLL
IP67 30W

Input voltage	220-240V AC
Frequency	50/60
Wattage (W)	30.0
IP	IP67
Protection class	Class II



B02E-X3375E-00
Fuente alimentación 12V SKOLL
IP67 75W

Input voltage	220-240V AC
Frequency	50/60
Wattage (W)	75.0
IP	IP67
Protection class	Class II

GIBSON 998A-L3306E-02 Surface Mounted Spotlight GIBSON IP65 LED SMD 6W 650lm CRI80
4000K 36° 150° Black

PRODUCTS OF THE SAME FAMILY



Gibson spike