

General info

Technical - Recessed


Indoor ceiling recessed projector with integrated LED sources, enhanced protection and direct light emission



| | |
|--------------|-------------------------|
| Ean | 8021696248790 |
| Item | DEEP FI 30W 4000K |
| Installation | Recessed (Ceiling) |
| Guarantee | 5 years |
| Gross weight | 0.9 kg |
| Volume | 0.005281 m ³ |

Technical info

| | |
|--------------------------|--|
| Net weight | 0.65 kg |
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | Separate, included Replaceable (by qualified operators only), electronic |
| Recessed specifications | Ø 200 - h. ≥ 100 , 3-40 |
| Front protection index | IP44 |
| Accessories not included | Dimmable driver |



Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 30 W |
| Emission | Direct |
| Max consupcion | max 30 W |
| Features LED | LED SMD |
| CCT | 4000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 80 |
| SDCM | - |
| Light beam | 77° |
| Light beam flux | 4350 lm |
| Useful light flux | 3150 lm |
| Standby power | < 0.50 W |