# ideal lux.





## General info

### **Technical - Spotlights and Tracks**

Indoor track mounted linear fitting with integrated LED sources and direct light emission

Ean	8021696283562
Item	DISPLAY ACCENT D1595 3000K BK
Installation	Eutrac 3-phase track (Ceiling)
Guarantee	5 years
Gross weight	1.98 kg
Volume	0.01734 m³

## **Technical info**

Net weight	1.57 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link on-off profile

1595 32

#### Source info

Interneted access	
Integrated source	Integrated LED module
Repleaceable source	Replaceable (by qualified operators only)
Power	40 W
Emission	Direct
Max consuption	max 40 W
Features LED	LED SMD SAMSUNG
ССТ	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 80
SDCM	3
Light beam	60°
UGR Maximum	< 16
Light beam flux	5300 lm
Useful light flux	4300 lm
Photobiological risk	1
Standby power	< 0.50 W

IDEAL LUX s.r.l. Via Taglio Destro, 32, 30035 Mirano (Venezia) Tel +39 041 5790500 | Fax +39 041 8872349 | E-mail info@ideal-lux.com www.ideal-lux.com