ideal lux.





General info


Technical - Spotlights and Tracks

Indoor track mounted linear fitting with integrated LED sources and direct light emission

Ean	8021696283685
Item	DISPLAY UGR D0535 3000K WH
Installation	Eutrac 3-phase track (Ceiling)
Guarantee	5 years
Gross weight	0.6 kg
Volume	0.006426 m ³

Technical info

Net weight	0.4 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link on-off profile



Source info

• •	
Integrated source	Integrated LED module
Repleaceable source	Replaceable (by qualified operators only)
Power	14 W
Emission	Direct
Max consuption	max 14 W
Features LED	LED SMD SAMSUNG
ССТ	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 80
SDCM	3
Light beam	70°
UGR Maximum	< 22
Light beam flux	2000 lm
Useful light flux	1150 lm
Photobiological risk	1
Standby power	< 0.50 W

IDEAL LUX s.r.l. Via Taglio Destro, 32, 30035 Mirano (Venezia) Tel +39 041 5790500 | Fax +39 041 8872349 | E-mail info@ideal-lux.com www.ideal-lux.com