


# Wall luminaire (Sconce)

## Rim 23W

Series: Rim    Article: MOD058WL-L25BK

|                       |                                     |
|-----------------------|-------------------------------------|
| Article               | MOD058WL-L25BK                      |
| Analogue              | MOD058WL-L25B3K;<br>MOD058WL-L25B4K |
| Brand                 | Maytoni                             |
| Collection            | Modern                              |
| Series                | Rim                                 |
| Product type          | Wall luminaire (Sconce)             |
| Fitting color         | Black                               |
| Fitting material      | Aluminum                            |
| IP protection         | IP 20                               |
| Dimmable              | Yes                                 |
| Height                | 400 mm                              |
| Width                 | 400 mm                              |
| Color rendering index | 80 CRI                              |
| Length                | 50 mm                               |
| Beam angle            | 120 °                               |
| Voltage               | 50Hz AC 220-240 V                   |
| Diameter              | 400 mm                              |
| Protection level      | Class1                              |
| Power                 | 23 W                                |
| Volume                | 0.0197 m³                           |
| Bowl length           | 150 mm                              |
| Bowl width            | 65 mm                               |
| Base length           | 150 mm                              |
| Base width            | 65 mm                               |



|                         |              |
|-------------------------|--------------|
| Energy efficiency class | G            |
| Fireproof               | No           |
| Packing length          | 470 mm       |
| Net                     | 1.07 kg      |
| Gross                   | 1.9 kg       |
| Service life            | 50000 h      |
| Control protocol        | Triac        |
| Luminous flux           | 500, 504     |
| Color temperature       | 3000, 4000 K |