

ELEGANTE

TRACK LIGHTING

AVAILABLE IN

made in
HOLLAND

Standard	Reflector					Led module		Mounting	
Dimmable	Reflector	Reflector	Reflector	Reflector	Reflector	Standard	DTW	1-phase	3-phase
									
Dim options			Fixture options						
Dimmable	Casambi	Honeycomb							
									
Lumen output					400lm				
CRI					>90Ra				
CCT					2700K • 3000K				

FIXTURE SPECIFICATIONS

 [View product on website](#)

Fixture weight: 200 grams



FIXTURE VARIATIONS

LED module	Lumen	Light colour	Efficiency (Lm/W)	Power	Dim options
Bridgelux V6 LED	400lm	927	80	6.0W	Triac / DALI / Casambi
Bridgelux V6 LED	400lm	930	83	6.0W	Triac / DALI / Casambi
Bridgelux V6 LED	400lm	Dim to Warm 1800K - 3000K	83	6.0W	Triac / DALI / Casambi

Fixture variations:

¹⁾ Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)

²⁾ Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerance of up to +/- 150 Kelvin compared to nominal value.

³⁾ Fixture efficiency is displayed in lumens per watt and is calculated based on the gross lumen output and power consumption of both the LED module and driver

⁴⁾ Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting without prior notice.

ARTICLE CODE CONFIGURATOR

IN

MOUNTING

LUMEN OUTPUT

LIGHT COLOUR

REFLECTOR

FIXTURE COLOUR

DIM OPTIONS

STANDARD

FIXTURE OPTIONS

Article code configurator:

¹⁾ This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome

POLAR

DIAGRAMS

