

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr


Bloc

VK/04264/W/W

Recessed adjustable spot zoomlight led, 2W, 3000K, 180lm, 15°-24°,
IP20, white



IP20

Dimensions	Gallery	Downloads																				
 5 cm 4.3cm  ø4.3 cm  Cut hole ø3.5cm  4.5cm	 Recessed Dark downlights Led Bloc  PhotoView Zoomlight <table><tr><th>Model</th><th>Power</th><th>Beam angle</th><th>Color temperature</th><th>Light output</th></tr><tr><td>VK/04264</td><td>2W</td><td>15°-24°</td><td>3000K</td><td>180lm</td></tr><tr><td>VK/04264</td><td>2W</td><td>15°-24°</td><td>4000K</td><td>180lm</td></tr><tr><td>VK/04264</td><td>2W</td><td>15°-24°</td><td>5000K</td><td>180lm</td></tr></table> Notes 1. The light fixture is designed for use in a recessed ceiling. 2. The light fixture is designed for use in a recessed ceiling. 3. The light fixture is designed for use in a recessed ceiling.	Model	Power	Beam angle	Color temperature	Light output	VK/04264	2W	15°-24°	3000K	180lm	VK/04264	2W	15°-24°	4000K	180lm	VK/04264	2W	15°-24°	5000K	180lm	  
Model	Power	Beam angle	Color temperature	Light output																		
VK/04264	2W	15°-24°	3000K	180lm																		
VK/04264	2W	15°-24°	4000K	180lm																		
VK/04264	2W	15°-24°	5000K	180lm																		

Technical Specifications	
Kelvin	3000K
Power	2W
Voltage	100-240V
Fitting	Recessed dark ceiling
Type	Downlight LED
Safety class	
Light source	OSRAM
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Clicks	20.000clicks
Zoomlight	
Working temperature	< 45°C
PAGE	208 Technical 2024
NICKNAME	Bloc

Physical Specifications	
Adjustable	
Recessed ceiling	Yes
Color	White
Material	Aluminium
Width	ø4.3cm
Length	ø4.3cm
Height	5cm
Net weight of product (kg)	0.06
Gross weight with inner box (kg)	0.08
Gross weight with master box (kg)	4.47
Cut out	ø3.5cm depth 4.5cm

Illumination Data	
Lumen	180lm
Beam angle	15°-24°
Lighting direction	
Dark light	Yes

Packing Info	
Pcs/carton	50pcs

Certification & Warranty	
Guarantee	3 years

Energy Label



VK LEADING LIGHT
VK/04264/W/W

A

B

C

D

E

F

G

2

kWh/1000h



2019/2015