

## General info

## Outdoor - Wall lamps


Outdoor wall mounted linear fitting with integrated LED sources and direct light emission



|                     |                         |
|---------------------|-------------------------|
| <b>Ean</b>          | 8021696246949           |
| <b>Item</b>         | ETERE AP COFFEE 4000K   |
| <b>Installation</b> | Wall                    |
| <b>Guarantee</b>    | 5 years                 |
| <b>Gross weight</b> | 0.7 kg                  |
| <b>Volume</b>       | 0.002733 m <sup>3</sup> |

## Technical info

|                              |  |
|------------------------------|--|
| <b>Net weight</b>            | 0.59 kg  |
| <b>Insulation class</b>      | I  |
| <b>Protection index</b>      | IP44   |
| <b>Compliance</b>            | CE   |
| <b>Operating temperature</b> | -15° ~ +45 °C  |
| <b>Dimmer</b>                | Non-dimmable, On-Off   |
| <b>Power output</b>          | 220-240 V AC 50/60 Hz  |
| <b>Power supply</b>          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |



## Source info

|                               |                       |
|-------------------------------|-----------------------|
| <b>Integrated source</b>      | Integrated LED module |
| <b>Replaceable source</b>     | No                    |
| <b>Power</b>                  | LED 10 W              |
| <b>Emission</b>               | Direct                |
| <b>Max consumption</b>        | max 10 W              |
| <b>Features LED</b>           | LED SMD               |
| <b>CCT LED</b>                | 4000 K                |
| <b>Duration LED (t. 25°C)</b> | 25000 h               |
| <b>CRI</b>                    | > 80                  |
| <b>Light beam flux</b>        | 1130 lm               |
| <b>Useful light flux</b>      | 790 lm                |
| <b>Standby power</b>          | < 0.50 W              |