ideal lux.





General info

Indoor - Suspensions

Technical info

Indoor suspended lamp with integrated LED sources and direct light emission

Ean	8021696276632
Item	FLY SP D90 4000K BIANCO
Installation	Suspension
Guarantee	5 years
Gross weight	9.5 kg
Volume	-

135 1310 410 006

Net weight	8.4 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	Replaceable (by qualified operators only),
	electronic
Front protection index	IP40
Accessories not included	Dimmable driver, uplight module

Source info

Integrated source	Integrated
Repleaceable source	Replaceal
Power	65 W
Emission	Direct
Max consuption	max 68,00
Features LED	LED SMD
CCT	4000 K
Duration LED (t. 25°c)	4000 K 50000 h
CRI	> 80
SDCM	3
Light beam	5 87°
UGR Maximum	< 19
Light beam flux	< 19 9900 lm
Useful light flux	5600 lm
Photobiological risk	1
-	
Standby power	< 0.50 W

Integrated LED module
Replaceable (by qualified operators only)
65 W
Direct
max 68,00 W
LED SMD SAMSUNG
4000 K
50000 h
> 80
3
87°
< 19
9900 lm
5600 lm
1
< 0.50 W