



<b>SKU</b>	: 670DB92725F0
<b>Housing Material</b>	: Aluminum Die Cast
<b>Housing Colour</b>	: Black (RAL9005)
<b>Luminaire Dimension [mm]</b>	: Ø50x124mm
<b>Optic</b>	: Reflector
<b>Reflector Colour</b>	: Metalized PC
<b>Beam Angle [deg]</b>	: 25°
<b>System Power [W]</b>	: 11.5W
<b>Luminous Flux [lm]</b>	: 1300lm
<b>System Efficiency [lm/W]</b>	: 113lm/W
<b>CCT [K]</b>	: 2700K
<b>CRI [Ra]</b>	: 90
<b>Chromaticity Tolerance</b>	: 3 MacAdam
<b>Mains Voltage [VAc]</b>	: 220-240V / 50 -60Hz
<b>Power Supply</b>	: Included ON/OFF
<b>Ambient Temperature [degC]</b>	: 35°C
<b>Ingress Protection</b>	: IP20
<b>Light Source Energy Class</b>	: E
<b>Light Source Identifier</b>	: BXRE-27G20FH-B-83
<b>Lifetime/Failure Rate [h]</b>	: 50000h/L80 B20
<b>Electrical Safety Class</b>	: Class II

---

<b>Net Weight [Kg]</b>	: 0.4Kg
<b>Certificates/Declarations</b>	: CE/UKCA
<b>Warranty [Y]</b>	: 5Y
<b>Light Source</b>	: 927 (2700K / CRI90)

---