



<b>SKU</b>	: 603GW93045F0
<b>Housing material</b>	: Aluminum Die Cast
<b>Luminaire Color</b>	: White
<b>Optic</b>	: Reflector
<b>Reflector Color</b>	: Specular Aluminium
<b>Power supply</b>	: Included ON/OFF
<b>Luminaire dimension</b>	: Ø70x180mm
<b>Cut out dimension</b>	: N/A
<b>Luminous Flux (lm)</b>	: 1650 lm
<b>LED power</b>	: N/A
<b>System power</b>	: 19W
<b>System efficiency</b>	: 87lm/W
<b>Beam angle (°)</b>	: 45°
<b>CCT (K)</b>	: 3000K
<b>CRI</b>	: 90
<b>Chromaticity tolerance</b>	: 3 MacAdam
<b>Nominal fA</b>	: N/A
<b>Nominal fV</b>	: N/A
<b>Mains Voltage</b>	: 220-240V / 50 -60Hz
<b>El. Class</b>	: Class I
<b>Lifetime</b>	: 50000h
<b>IP rating</b>	: IP20

<b>Light source energy class</b>	: E
<b>Light source identifier</b>	: L2C5-30901205F1300
<b>Net. Weight</b>	: 0.92Kg
<b>Warranty</b>	: 5Y

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K. Technical data can change without prior notice.

©2022 Karizma Luce BV. All rights reserved. Please visit [karizmaluce.com](http://karizmaluce.com) for more information.