

FLOS

F1367021 Mud

Smithfield Suspension Pro

Designed by Jasper Morrison, 2009



45W - 2791lm - 2700K - CRI> 95

Suspension lamp with direct light. Aluminium body. Available in gloss black, matt black, red, green, white or MUD. Injection-moulded opalescent methacrylate diffuser. Steel ceiling attachment with steel suspension cable, 5 pole electric cable in PTFE double insulation, working length 2700mm.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8059607014967
Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	45
Lumen Output (lm)	2791

Physical

Colour	Mud
Length (mm)	600
Cord colour	Clear
Cord length (mm)	2700
Canopy colour	Mud
Canopy length/diameter (mm)	146
Canopy height (mm)	36
Net weight (kg)	5.8
Package height (mm)	310
Package width (mm)	710
Package length (mm)	710
Package volume (m3)	0.16
IP internal	20



Download

Mounting instructions [↓ PDF](#)

Photometric Files


LDT / IES [↓ LDT](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



Photometric


Light distribution	Roto symmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable Push
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Spare Parts



01.	Smithfield Mud rose assembly	RA3690221
02.	Kit of 5 or rings	RF05382
03.	Smithfield Suspension 2,7mt	RF29934
	fep/pvc 5x0,75 transparent cable	
04.	3 mt steel cable ø1,2 with 19	RF29665
	winded wires	
05.	Driver 60W 500-1400mA 200-	RF31674
	240V	
06.	Methacrylate diffuser	RF19022

RF29934

Smithfield Suspension 2,7mt
fep/pvc 5x0,75 transparent cable



RA3690221

Smithfield Mud rose assembly

RF05382

Kit of 5 or rings

RF29665

3 mt steel cable ø1,2 with 19
winded wires



RF31674

Driver 60W 500-1400mA 200-
240V

RF19022

Methacrylate diffuser